




ASTORI CALL OUT		SIZES	FIELD OF APPLICATION AND MATERIALS			REFERENCE STANDARDS			NOTES
<b>ANCHOR NUTS CORNER 90°</b>									
	PO300	6-32÷5/16	900MPa	235°C	25CrMo4	MS21055	NAS684		
	PO301		900MPa	425°C	A286	MS21056	NAS684C		
	PO302		1100MPa	235°C	25CrMo4	NAS1772			
	PO303		1100MPa	425°C	A286	NAS1772C			
	O300	3÷10	900MPa	235°C	25CrMo4	LN29675			
	O301		900MPa	425°C	A286				
	O310		900MPa	235°C	25CrMo4	LN29988	LN65131		
	O311		900MPa	425°C	A286				
	JO310		1100MPa	235°C	25CrMo4	DIN65238	EN2862		
	JO311		1100MPa	425°C	A286	DIN65239	EN2863	EN4251	
	PO330	8-32÷1/4	900MPa	235°C	25CrMo4	MS21057	NAS685		
	PO331		900MPa	425°C	A286	MS21058	NAS685C		
	O330	4÷8	900MPa	235°C	25CrMo4	LN29676			
	O331		900MPa	425°C	A286				
	PO350	4-40÷1/4	900MPa	235°C	25CrMo4	MS21073	NAS698		
	PO351		900MPa	425°C	A286	MS21074			
	PO352		1100MPa	235°C	25CrMo4	NAS1777			
	PO353		1100MPa	425°C	A286	NAS1777C			
	O350	4÷6	900MPa	235°C	25CrMo4				
	O351		900MPa	425°C	A286				
	O360		900MPa	235°C	25CrMo4	LN29989			
	O361		900MPa	425°C	A286				
	JO360		1100MPa	235°C	25CrMo4	EN2855			
	JO361		1100MPa	425°C	A286	EN3750	EN4252	JN0226	